






**TLR-7® X sub/ TLR-7® X sub USB**

**COMPACT, RAIL-MOUNTED TACTICAL LIGHT DESIGNED FOR USE WITH GLOCK® 43X MOS, 48 MOS, 43X RAIL, AND 48 RAIL SUBCOMPACT HANDGUNS**

- DESCRIPTION:** The TLR-7® X sub features multi-fuel battery capability – powered by either one (1) CR123A or one (1) Streamlight SL-B9® lithium-ion rechargeable battery pack, delivering up to 725 lumens and 7,700 candela. The integrated rail clamp is designed to rapidly attach/detach from the side of the weapon, providing smooth installation and removal without having to put your hands in front of the muzzle. Features a specialized clamp system for mounting on GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X rail and GLOCK® 48 rail. Please refer to [streamlight.com](http://streamlight.com) for the current compatibility list.
- CASE MATERIAL:** Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish.  
Switch housing: Impact- and chemical-resistant engineered polymer.
- DIMENSIONS:** Width: 1.16 in (2.95 cm)      Height: 1.24 in (3.15 cm)      Length: 2.51 in (6.38 cm)
- WEIGHT:** CR123A: 2.39 oz (67.8 g) with battery.  
SL-B9®: 2.64 oz (74.8 g) with battery.
- LENS:** High temperature, shock-mounted, impact-resistant, scratch resistant BOROFLOAT® glass.
- LIGHT SOURCE:** White LED, impervious to shock with a 50,000-hour lifetime.
- LIGHT OUTPUT:** CR123A: 550 lumens, 5,000 candela peak beam intensity, and 141m beam distance.  
SL-B9®: 725 lumens, 7,700 candela peak beam intensity, and 176m beam distance.  
Custom TIR optic produces a concentrated beam with optimum peripheral illumination.  
Optimized electronics provide regulated intensity.
- ON/OFF:** Rear switches left and right of trigger guard provide ambidextrous operation.  
Momentary and constant on operation.  
User-activated strobe.
- RUN TIME:** CR123A: 1.5 hours of continuous operation to the 10% output level.  
SL-B9®: 1 hour of continuous operation to the 10% output level.
- BATTERY:** CR123A: One (1) 3-volt CR123A lithium battery with a storage life of 10 years.  
SL-B9®: One (1) Streamlight Li-Ion 850mAh USB-C rechargeable battery pack with integrated safety circuit, rechargeable up to 500 cycles. Battery installed/removed through face cap. No need to remove from firearm. Charges within 2.5 hours via USB-C cord or optional bank charger.
- FEATURES:** Multi-fuel operation; SL-B9® Li-Ion rechargeable battery pack or CR123A.  
High-power LED for extreme brightness.  
Ambidextrous operation.  
One-handed snap on and tighten interface keeps hands away from muzzle when attaching or detaching.  
Extensively live fire tested.  
Operating temperature: -40° F to +120° F (CR123A) or -4° F to +120° F (SL-B9®).  
IPX7-rated design; waterproof to 1 meter for 30 minutes.  
Serialized for positive identification.
- APPROVALS:**  Meets applicable United Kingdom and European Community Directives  
 CEC Compliant (with SL-B9® only)  
 TAA Compliant
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** SL-B9® Li-Ion Battery Bank Charger

All Rights Reserved. GLOCK® is a registered trademark of GLOCK, Inc. Streamlight has not sought endorsement of this product from GLOCK, Inc.  
BOROFLOAT® is a registered trademark of SCHOTT AG.